

**NAME**

sendnews - send news articles via mail

**SYNOPSIS**

sendnews [-o] [-a] [-b] [-n newsgroups] destination

**DESCRIPTION**

sendnews reads an article from its standard input, performs a set of changes to it, and gives it to the mail program to mail it to destination.

An 'N' is prepended to each line for decoding by uuvec(1).

The **-o** flag handles old format articles.

The **-a** flag is used for sending articles via the **ARFANET**. It maps the article's path from uuvechost!xxx to xxx@arcnethost.

The **-b** flag is used for sending articles via the **Berknet**. It maps the article's path from uuvechost!xxx to berkhost!xxx.

The **-n** flag changes the article's newsgroup to the specified **NEWSGROUP**.

**SEE ALSO**

inews(1), uuvec(1), recnews(1), readnews(1), newscheck(1)

NAME

SYNOPSIS

DESCRIPTION

1. This is a description of the system. It is a system that is used for the purpose of... (faint text)

2. The system is designed to be used by... (faint text)

3. The system is designed to be used by... (faint text)

4. The system is designed to be used by... (faint text)

5. The system is designed to be used by... (faint text)

6. The system is designed to be used by... (faint text)

7. The system is designed to be used by... (faint text)

8. The system is designed to be used by... (faint text)

9. The system is designed to be used by... (faint text)

10. The system is designed to be used by... (faint text)

SEE ALSO

(faint text)